



Height: 2 1/2" Width: 7 5/8"

**RDL6-ADJ-27K RDL6-ADJ-30K  
RDL6-ADJ-41K RDL6-ADJ-50K**

**6" LED Adjustable Baffle Trim**

Isolated driver for improved thermal management.

**ELECTRICAL SPECIFICATIONS:**

- Voltage: 120V AC
- Wattage: 12W
- Power factor: 90% +

**LIGHTING SPECIFICATIONS:**

- LED type/brand: EPISTAR chip (COB)
- Driver-36,000-hour design life
- Dimmable: Yes
- Lumens: 900 lm
- Color temperature: 2700K, 3000K (Warm white), 4100K(Natural white) and 5000K (Daylight)
- CRI: 90

**WARRANTY:**

- Five-year warranty

MODEL NO	WATTS	LUMENS	VOLTAGE	COLOR TEMP
RDL6-ADJ-27K	12W	900LM	120V AC	2700K
RDL6-ADJ-30K	12W	900LM	120V AC	3000K
RDL6-ADJ-41K	12W	900LM	120V AC	4100K
RDL6-ADJ-50K	12W	900LM	120V AC	5000K

**HOUSING SPECIFICATIONS:**

- Housing: Spun aluminum with white powder coat finish
- Trim ring: Integrated spun aluminum white powder coat finish
- Gasket: Close cell Neoprene foam gasket
- Lens: 0.125" white translucent acrylic
- Wet locations: Suitable for damp locations
- Maximum ambient 4°C (104°F)

**CERTIFICATIONS:**

- UL listed
- Energy Star-rated (2700K, 3000K, and 4100K)
- Pending Energy Star rating for 5000K version

